KITCHEN AND CANTEEN

DOOR SCHEDULE

REFERENCE POSITION	EXTERNAL DOUBLE SWING DOOR ON GLASS & BRICK WALL BY CANTEEN	SINGLE DOOR ON BRICK WALL(TOILET DOORS)	TOILET DUCT DOOR ON BRICK WALL	PARAPLEGIC TOILET DOOR	DOUBLE DOOR BY THE RECEIVING AREA	STANDARD ROOM DOORS	FIRE EXIT DOOR	DOUBLE INTERNAL DOORS ON BRICK WALL BY TROLLEY & DISH TRANSFER AREA	FEMALE CHANGE ROOM TOILET LOBBY DOOR
ELEVATION									
DOOR TYPE	D01	D02	D03	D04	D05	D06	D07	D08	D09
DESCRIPTION	1800*2400MM ALUMINIUM DOUBLE SWING DOOR POWDERCOATED ALUMINIUM FRAME WITH 6.38MM LAMINATED SINGLE GLAZING.	813*2032MM PLAIN SEMI SOLID-CORE-FLUSH PANEL INTERNAL QUALITY DOOR PROTECTED WITH HARDWOOD LIPPINGS TO ALL EDGES. SINGLE LEAF.	750*2032MM WIDE STYLE SINGLE LEAF ALUMINIUM DOOR WITH LAZY "Z" LOUVRES	44MM THICK SOLID CORE FLUSH PANEL DOOR(SWING) WITH EXPOSED HARD WOOD EDGES ALL ROUND AND 3.2MM TIMBER VENEER (WOODCOVERING) TO BOTH SIDES.1000*2032MM.	FLUSH PANEL: SOLID CORE DOOR , PAINTED FRAME TO HAVE 3NO HINGES. 150mm STAINLESS STEEL PUSH PLATE & KICK PLATE FULL DOOR WIDTH, BOTH SIDES	900 *2032MM PLAIN SEMI SOLID-CORE-FLUSH PANEL INTERNAL QUALITY DOOR PROTECTED WITH HARDWOOD LIPPINGS TO ALL EDGES. SINGLE LEAF.	900 *2032MM PLAIN SEMI SOLID-CORE-FLUSH PANEL EXTERNAL QUALITY DOOR PROTECTED WITH HARDWOOD LIPPINGS TO ALL EDGES. SINGLE LEAF.	FLUSH PANEL: SOLID CORE DOOR OPENING 180°. PAINTED. HEAVY DUTY FLOOR SPRING WITH STAINLESS STEEL COVER. 1000mm STAINLESS STEEL PUSH PLATE & KICK PLATE FULL DOOR WIDTH, BOTH SIDES WITH 6.38mm SHATTER PROOF CLEAR GLSS	813*2032MM PLAIN SEMI SOLID-CORE-FLUSH PANEL INTERNAL QUALITY DOOR PROTECTED WITH HARDWOOD LIPPINGS TO ALL EDGES. SINGLE LEAF.
ACCESSORIES		STAINLESS STEEL PUSH PLATE & KICK PLATE FULL DOOR WIDTH BOTH SIDES		1no aluminium ventilation door grille (Europair) size 450x200mm with concealed fixing.		STAINLESS STEEL PUSH PLATE & KICK PLATE FULL DOOR WIDTH BOTH SIDES			STAINLESS STEEL PUSH PLATE & KICK PLATE FULL DOOR WIDTH BOTH SIDES
FRAME	ALUMINIUM FRAME NATURAL ANODISED ALUMINIUM FRAME SECTIONS TO SUIT DOOR TYPE AND SIZE	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	ALUMINIUM FRAME ALUMINIUM DOOR FRAME SECTIONS TO SUIT DOOR TYPE AND SIZE PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032MM.THE MIDDLE TRANSOM PREPREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES
WALL	GLASS WALL / 395mm	115mm / 230mm		230mm / 280mm	230mm / 280mm	230mm / 230mm	230mm / 280mm	115mm / 230mm	230mm / 280mm
DOOR N° AS INDICATED ON PLAN	D01|L0/01 D01|L0/02 D01|L0/03 D01|L0/04	D02|L0/05 D02|L0/06 D02|L0/07 D02|L0/08 D02|L0/09 D02|L0/10 D02|L0/12 D02|L0/13 D02|L0/14 D02|L0/15 D02|L0/32 D02|L0/33 D02|L0/34 D02|L0/37 D02|L0/38 D02|L0/42	D03|L0/11 D03|L0/39 D03|L0/41	D04|L0/16 D04|L0/44	D05|L0/30	D06|L0/17 D06|L0/20 D06|L0/21 D06|L0/22 D06|L0/26 D06|L0/28 D06|L0/29 D06|L0/31 D06|L0/40 D06|L0/41	D07|L0/27	D08|L1/18 D08|L1/19	D09|L0/35
TOTAL DOORS									
IRONMONGERY	IM-22	IM-04	IM-03	IM-15	IM-39	IM-24	IM-33	IM-40	IM-12

KITCHEN AND CANTEEN

DOOR SCHEDULE

REFERENCE POSITION	CANTEEN PARTITION DOORS	DOUBLE HANDING GAS BOTTLE CAGE GATE	MALE CHANGE TOILET LOBBY DOOR	FIRE EXIT DOOR
ELEVATION				
DOOR TYPE	D10	D11	D12	D13
DESCRIPTION	ALUGLASS BAUTECH VARIFLEX® VX110 MOBILE ACOUSTIC (OPERABLE WALL) PARTITION, SIZE 5770MM X 3000 HIGH TO SUIT STRUCTURAL OPENING SIZE 5770MM X 3000 HIGH. COMPRISING 110MM THICK TONGUED AND GROOVED ACOUSTICALLY DECOUPLED 5108 RW (50DB STC) RATED PANELS WITH FOLKSTONE GREY MELAWOODVENEER FINISH, WITH MECHANICALLY RETRACTABLE TOP AND BOTTOM SEALS AND VERTICAL SEALS FORMED OF ALUMINIUM EXTRUSIONS WITH LIP SEALS AND MAGNETIC STRIPS. PANELS SUSPENDED AT ONE ROLLER TROLLEY PER PANEL ON TRACK WITH BALL BEARING AND/OR THRUST ROLLERS WITH TRACK BOLTED TO SUSPENSION PLATES IN TURN BOLTED TO STEEL SUPPORT STRUCTURE AND 0MM HIGH ACOUSTIC BAFFLE/BULKHEAD TO SPECIFIED 5108 STC CLASS OF THE PANELS FITTED TO AND ABOVE TRACK IN CEILING VOID. PANELS ARE TO PARK NICHE CROSSWISE UNDER TRACK WITH PANELS STACKING CROSSWISE UNDER TRACK.	50x50mm HOLLOW SECTION FRAME WITH VALMETEX FLATTENED MESH REF.V.E.M 6332/E WELDED TO THE FRAME.	.813*2032MM PLAIN SEMI SOLID-CORE-FLUSH PANEL INTERNAL QUALITY DOOR PROTECTED WITH HARDWOOD LIPPINGS TO ALL EDGES. SINGLE LEAF.	900 *2032MM PLAIN SEMI SOLID-CORE-FLUSH PANEL EXTERNAL QUALITY DOOR PROTECTED WITH HARDWOOD LIPPINGS TO ALL EDGES. SINGLE LEAF.
ACCESSORIES			STAINLESS STEEL PUSH PLATE & KICK PLATE FULL DOOR WIDTH BOTH SIDES	
FRAME		HOLLOW SQUARE SECTION	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES	PRESSED STEEL FRAME SINGLE REBATE13*2032 WITH 305 FANLIGHT ,THE MIDDLE TRANSOM PRE-PREPARED TO RECEIVE DOOR CLOSER COMPLETE WITH TIE BARS.LAGS & 1-1/2 PAIRS OF STEEL BUTT HINGES
WALL				
DOOR N° AS INDICATED ON PLAN	D10|L0/45 D10|L0/46 D10|L0/47 D10|L0/48	D11|L0/25	D12|L0/36 D12|L0/43	D13|L0/23 D13|L0/24
TOTAL DOORS				
IRONMONGERY	BY ACOUSTIC DOOR MANUFACTURER	IM-11	IM-04	IM-24

1 DOOR SCHEDULE
NTS

GENERAL NOTES:

1. NO DIMENSIONS TO BE SCALED.
2. DIMENSIONS TO BE VERIFIED ON SITE BEFORE COMMENCING ANY SITE WORK OR SHOP DRAWINGS.
3. DIMENSIONS ARE TAKEN TO CENTRE LINES OR STRUCTURAL SURFACES AND DO NOT INCLUDE FINISHES EXCEPT WHERE OTHERWISE STATED.
4. THE ARCHITECT IS TO BE NOTIFIED OF ANY DISCREPANCIES BETWEEN THIS DRAWING AND ANY OTHER DRAWING OR CONSTRUCTION DOCUMENTS INCLUDING THOSE ISSUED BY CONSULTANTS AND NOMINATED SUB-CONTRACTORS BEFORE COMMENCING WORK.
5. MINIMUM STRENGTH POF CONCTRETE 21Mpa

ISSUED FOR MEASUREMENT PURPOSES

REV.	DESCRIPTION	DATE
C	ISSUED FOR STAGE 3 COORDINATION	04/02/22

CLIENT
SOUTHERN AFRICAN DEVELOPMENT COMMUNITY

JOB TITLE
SADC STANDBY FORCE REGIONAL LOGISTICS DEPOT, AT RASESA, GABORONE, BOTSWANA,

DWG TITLE
KITCHEN & CANTEEN - DOOR SCHEDULE

SCALE	AS SHOWN	JOB No.	G649
DATE	FEBRUARY 2022	DRAWN BY	KT
REV.	C	CHECKED BY	AM

Project Team:

Architect	FMA Architects
Quantity Surveyor	Turner & Townsend (Pty) Ltd,
Electrical Engineers	G4 Consulting Engineers (Pty) Ltd,
Mechanical Engineers	G4 Consulting Engineers (Pty) Ltd,
Civil Engineers	Bothakga Barrow Botswana (Pty) Ltd,
Structural Engineers	Bothakga Barrow Botswana (Pty) Ltd,

FMA ARCHITECTS (PTY) LTD.
P.O. BOX 201504 BONTLENG
GABORONE, BOTSWANA.
TEL: 3959812/3 FAX: 3959814
E-MAIL: fmagabs@info.bw

DRWG. No.
G649-SADC/ARCH/012/1-403